




PCT/EP200 4 / 0 0 3 9 9 2



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

**PRIORITY  
DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)




I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 25 March 2004

**BEST AVAILABLE COPY**



The  
Patent  
Office

14MAY03 E806929-1 002898  
POL/7700 0.00-0310974.1

The Patent Office

Cardiff Road  
Newport  
Gwent NP10 8QQ

**Request for grant of a patent**  
(See the notes on the back of this form. You can also get  
an explanatory leaflet from the Patent Office to help  
you fill in this form)

1. Your reference

C4305(C)/lh

2. Patent application number  
(The Patent Office will fill in this part)

0310974.1

13 MAY 2003

3. Full name, address and postcode of the or of  
each applicant (*underline all surnames*)

UNILEVER PLC  
UNILEVER HOUSE, BLACKFRIARS  
LONDON, EC4P 4BQ

Patents ADP number (*if you know it*)

50426956002

If the applicant is a corporate body, give the  
country/state of its incorporation

UNITED KINGDOM

4. Title of the invention

FABRIC CONDITIONING COMPOSITIONS

5. Name of your agent (*if you have one*)

ELLIOTT, Peter William

"Address for Service" in the United Kingdom  
to which all correspondence should be sent  
(including the postcode)

PATENT DEPARTMENT, UNILEVER PLC  
COLWORTH HOUSE, SHARNBROOK  
BEDFORD, MK44 1LQ

Patents ADP number (*if you know it*)

6. If you are declaring priority from one or more  
earlier patent applications, give the country  
and the date of filing of the or of each of these  
earlier applications and (*if you know it*) the or  
each application number

Country	Priority application number ( <i>if you know it</i> )	Date of filing (day / month / year)
---------	--	--

1628003

7. If this application is divided or otherwise  
derived from an earlier UK application,  
give the number and the filing date of  
the earlier application

Number of earlier application

Date of filing  
(day/month/year)

8. Is a statement of inventorship and of right  
to grant of a patent required in support of  
this request? (*Answer 'Yes' if:*

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an  
applicant, or
- c) any named applicant is a corporate body.  
See note (d))

YES

# Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 23

Claim(s) 3

Abstract 1

Drawing(s)

10. If you are also filing any of the following, state how many against each item.

Priority Documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature(s) *Leonie Watkinson* Date: 13/05/03

Leonie WATKINSON, Authorised Signatory

12. Name and daytime telephone number of person to contact in the United Kingdom

Louise Holland, Tel 01234 22 2082

## Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

## Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

- 1 -

FABRIC CONDITIONING COMPOSITIONSField of the Invention

5

The present invention relates to fabric conditioning compositions. More specifically, the present invention relates to fabric conditioning compositions comprising specific nonionic surfactants which provide excellent high  
10 temperature stability.

Background and Prior Art

15 Fabric treatment compositions for treatment of fabrics during a laundry operation are well known. They are typically divided into the classes of domestic or industrial compositions, main-wash or rinse cycle compositions and cleaning or conditioning/softening compositions.

20 Fabric conditioning compositions typically comprise a fabric conditioning agent, such as a fabric softening material, at a level of about 1 to less than about 10% by weight in which case the composition is considered to be dilute or semi-concentrated, or from more than about 10 to about 30% by  
25 weight, in which case the composition is considered to be concentrated.

While it has hitherto been known that so-called concentrated compositions are particularly prone to instability, such as  
30 phase-separation, flocculation, gelling, pearlescence etc, upon storage, it was generally considered that such problems did not exist for so-called dilute compositions.

In particular, it was conventional understood and believed that the level of components typically known to induce instability, such as perfumes, nonionic surfactants and quaternary ammonium fabric softening materials, was sufficiently low that their destabilising influence was negligible.

Instability, particularly upon storage at elevated temperatures, often manifests itself as pearlescence or as an irreversible thickening of the composition to the point that it may no longer be pourable. This is clearly undesirable to consumers.

Storage stability at elevated temperatures has previously been addressed in various ways. WO-A1-99/50378 discloses a fabric softening agent comprising from 1 to 8% of a quaternary ammonium fabric conditioning compound, a stabilising agent and a fatty alcohol. The stabilising agent is preferably a primary or secondary alkoxylated alcohol comprising 10 or more moles of alkylene oxide.

The present inventors have found that, while stability upon storage at an elevated temperature of 37°C is desirable, it can be achieved, for dilute compositions at least, without significant difficulty. However, stability at even higher temperatures, e.g. 41°C or 45°C or even 50°C, as can be experienced for extended periods in certain environments, is disproportionately more difficult to achieve.

30

---

This problem is exacerbated when the composition comprises an ester-linked quaternary ammonium fabric softening

material and is further complicated when the material has one or more fully saturated alkyl chains.

5 However, it is desirable to use ester-linked compounds due to their inherent biodegradability and to use substantially fully saturated quaternary ammonium fabric softening compounds due to their excellent softening capabilities and because they are more stable to oxidative degradation (which can lead to malodour generation) than partially saturated or 10 fully unsaturated quaternary ammonium softening compounds.

Of the types of ester-linked quaternary ammonium materials known, it is desirable to use those based on triethanolamine which produce at least some mono-ester linked component and 15 at least some tri-ester linked component since the raw material has a low melting temperature which enables the manufacturing process of the composition to occur at low temperatures. This reduces difficulties associated with high temperature handling, transport and processing of the 20 raw material and compositions produced therefrom.

#### Objects of the Invention

25 The present invention seeks to address one or more of the above-mentioned problems, and, to give one or more of the above-mentioned benefits desired by consumers.


#### Summary of the Invention

30 Thus, according to the present invention there is provided a fabric conditioning composition comprising:

(a) an ester-linked quaternary ammonium fabric softening

material; and

(b) a nonionic material represented by formula (I):-



wherein R and R' are independently selected from C<sub>1</sub> to C<sub>15</sub> optionally substituted alkyl, alkenyl, hydroxyalkyl and benzyl groups and the combined number of carbons in R and R' is from 7 to 16, n is from 1 to 9 and a is 2 or 3.

15 In the context of the present invention, it is to be understood that n relates to the average degree of alkoxylation in any given sample.

20 According to a further aspect of the present invention, there is provided the use of a compound of formula (I) in a fabric conditioning composition to improve the elevated temperature storage stability of the fabric conditioning composition.


25 In the context of the present invention, the term "comprising" means "including" or "consisting of". That is the steps, components, ingredients, or features to which the term "comprising" refers are not exhaustive.

Detailed Description of the Invention

The compositions of the present invention are preferably  
rinse conditioner compositions, more preferably aqueous  
5 rinse conditioner compositions for use in the rinse cycle of  
a domestic laundry process.

**Nonionic Material**

10 The compositions of the invention comprise a nonionic  
material of formula (I):



20 wherein R and R' are independently selected from C<sub>1</sub> to C<sub>15</sub>  
optionally substituted alkyl, alkenyl, hydroxyalkyl and  
benzyl groups and the combined number of carbons in R and R'  
is from 7 to 16, n is from 1 to 9 and a is 2 or 3.

25 Preferably the total number of carbons in R and R' is from 8  
to 15, more preferably 10 to 15, most preferably 11 to 15.

Preferably n is from 2 to 8, more preferably from 2 to 6,  
most preferably from 2 to 5, e.g. from 2 to 4.

30


Suitable materials of this class include Tergitol 15-S-3, ex  
Union Carbide (a mixture of linear C<sub>11</sub>-C<sub>15</sub> secondary

alcohols reacted with 3 moles of ethylene oxide); Lutensol TO3, ex BASF (a saturated nonionic surfactant based on C13 branched alcohols, with 3 moles of ethylene oxide); KX-NS12030, 14030 and Softanol 30, ex Nippon Shokubai (a mixture of secondary alcohols ethoxylated with 3 moles of ethylene oxide); Ethylan CD802, ex Across Chemicals (a synthetic branched chain alcohol reacted with 2 moles of ethylene oxide); Chemal 2EH-2, ex Chemax (a polyethyleneoxy, 2-ethylhexyl ether reacted with 2 moles of ethylene oxide); Remcopal 273, ex Atochem and Synperonic 10/3, ex ICI (both being mixtures of branched and linear C10 alcohols reacted with 3 moles of ethylene oxide); and Prox-onic 2EHA, ex Protex (a 2-ethylhexyl ether reacted with 2 moles of ethylene oxide).

It is particularly preferred that the weight ratio of quaternary ammonium material to nonionic surfactant is in the range from 1:10 to 100:1, more preferably 1:1 to 75:1, even more preferably from 1.5:1 to 50:1, most preferably 2:1 to 10:1


#### Other Nonionic Surfactants

Although not essential, other nonionic surfactants may be present in the compositions. Suitable nonionic surfactants of this type can be represented by the general formula:



where R is selected from the group consisting of primary, secondary and branched chain alkyl and/or acyl hydrocarbyl groups; primary, secondary and branched chain alkenyl hydrocarbyl groups; and primary, secondary and branched

chain alkenyl-substituted phenolic hydrocarbyl groups; the hydrocarbyl groups having a chain length of from 8 to about 25, Y is:



in which R has the meaning given above or can be hydrogen; and Z is 10 or more.

10   It is preferred that the level of such nonionic materials is low in the compositions of the invention because nonionic surfactants of this type can have a destabilising influence on the compositions, particularly upon storage at very high temperatures.

15

#### Quaternary ammonium fabric softening material

The fabric conditioning material used in the compositions of the present invention comprises one or more quaternary  
20   ammonium materials which are ester-linked. Preferably the quaternary ammonium material comprises at least one mono-ester linked component and at least one tri-ester linked component.

25   By mono-, di- and tri-ester linked components, it is meant that the quaternary ammonium softening material comprises, respectively, a quaternary ammonium compound comprising a single ester-link with a fatty hydrocarbyl chain attached thereto, a quaternary ammonium compound comprising two  
30   ester-links each of which has a fatty hydrocarbyl chain attached thereto, and a quaternary ammonium compound comprising three ester-links each of which has a fatty hydrocarbyl chain attached thereto.

Below is shown typical levels of mono-, di- and tri-ester components in a fabric softening material used in the compositions of the invention.

5

The level of the mono-ester linked component of the quaternary ammonium material used in the compositions of the invention is preferably between 8 and 40% by weight, based on the total weight of the raw material in which the quaternary ammonium material is supplied.

10

The level of the tri-ester linked component is preferably between 20 and 50% based on the total weight of the raw material in which the quaternary ammonium material is supplied.

15

Preferably, the average chain length of the alkyl or alkenyl group is at least C<sub>14</sub>, more preferably at least C<sub>16</sub>. Most preferably at least half of the chains have a length of C<sub>18</sub>.


20

It is generally preferred if the alkyl or alkenyl chains are predominantly linear.


25

A preferred ester-linked quaternary ammonium cationic softening material suitable for use in the invention is represented by the formula:

---



wherein each R is independently selected from a C<sub>5-35</sub> alkyl or alkenyl group, R<sup>1</sup> represents a C<sub>1-4</sub> alkyl or hydroxyalkyl group or a C<sub>2-4</sub> alkenyl group,




n is 0 or an integer selected from 1 to 4, m is 1, 2 or 3 and denotes the number of moieties to which it refers that pend directly from the N atom, and X<sup>-</sup> is an anionic group, such as halides or alkyl sulphates, e.g. chloride, methyl sulphate or ethyl sulphate.

Especially preferred materials within this class are di-alkyl and di-alkenyl esters of triethanol ammonium methyl sulphate. Commercial examples of compounds within this formula are Tetranyl AHT-1 (di-hardened tallowyl ester of triethanol ammonium methyl sulphate 85% active), L1/90 (partially hardened tallow ester of triethanol ammonium methyl sulphate 90% active), and L5/90 (palm ester of triethanol ammonium methyl sulphate 90% active), all ex Kao corporation), Rewoquat WE18 and WE20 (both are partially hardened tallow ester of triethanol ammonium methyl sulphate

90% active), both ex Goldschmidt Corporation and Stepantex VK-90 (partially hardened tallow ester of triethanol ammonium methyl sulphate 90% active), ex Stepan Company).


- 5 A second group of cationic fabric softening compounds suitable for use in the invention is represented by formula:



- wherein each  $\text{R}^1$  group is independently selected from  $\text{C}_{1-4}$  alkyl, hydroxyalkyl or  $\text{C}_{2-4}$  alkenyl groups; and wherein each  $\text{R}^2$  group is independently selected from  $\text{C}_{8-28}$  alkyl or alkenyl groups;  $n$  is 0 or an integer from 1 to 5 and  $\text{T}$  and  $\text{X}^-$  are as defined above.

- 20 Preferred materials of this class such as 1,2 bis[tallowyloxy]-3- trimethylammonium propane chloride and 1,2-bis[oleyloxy]-3-trimethylammonium propane chloride and their method of preparation are, for example, described in US 4137180 (Lever Brothers), incorporated herein.
- 25 A third group of cationic fabric softening compounds suitable for use in the invention is represented by formula:
-

- 11 -



5

10

wherein each  $R^1$  group is independently selected from  $C_{1-4}$  alkyl, or  $C_{2-4}$  alkenyl groups; and wherein each  $R^2$  group is independently selected from  $C_{8-28}$  alkyl or alkenyl groups;  $n$  is 0 or an integer from 1 to 5 and  $T$  and  $X^-$  are as defined above.

15

A preferred material of this class is di(tallowoyloxyethyl)-dimethyl ammonium chloride.

#### Iodine Value of the Parent Fatty Acyl group or Acid

20

25

The iodine value of the parent fatty acyl compound or acid from which the quaternary ammonium fabric softening material is formed is preferably from 0 to 120, preferably from 0 to 95, more preferably from 0 to 60. It is particularly preferred that the iodine value of the parent fatty acid or acyl group from which the quaternary ammonium fabric softening material is formed is from 0 to 25, more preferably from 0 to 10, most preferably from 0 to 5, e.g. 0 to 4 or even 0 to 2. That is, it is preferred that the alkyl or alkenyl chains are substantially fully saturated.

The iodine value, referred to above, represents the mean iodine value of the parent fatty acyl compounds or fatty acids of all of the quaternary ammonium materials present.

- 5 In the context of the present invention, iodine value of the parent fatty acyl compound or acid from which the fabric softening material formed, is defined as the number of grams of iodine which react with 100 grams of the compound.
- 10 The method for calculating the iodine value is as described in WO-A1-01/04254.

The quaternary ammonium fabric softening material is preferably present in an amount from 1 to 80% by weight  
15 based on the total weight of the composition, more preferably 1.5 to 60% by weight, most preferably 1.7 to 40% by weight, e.g. 2-25% by weight.

#### Fatty complexing agent

20

It is especially preferred that the compositions of the present invention comprise a fatty complexing agent.

Especially suitable fatty complexing agents include fatty  
25 alcohols and fatty acids. Of these, fatty alcohols are most preferred.

Preferred fatty acids include hardened tallow fatty acid (available under the tradename Pristerene, ex Uniqema).

30

---

Preferred fatty alcohols include hardened tallow alcohol, available as Stenol and Hydrenol (ex Cognis), and Laurex CS

- 13 -

(ex Albright and Wilson) and behenyl alcohol, available as Lanette 22 (ex Henkel).

- The fatty complexing agent is preferably present in an amount from 0.01 to 15% by weight based on the total weight of the composition. More preferably, the fatty component is present in an amount of from 0.1 to 10%, most preferably from 0.2 to 5%, e.g. 0.3 to 4% by weight.
- 10 If the quaternary ammonium material comprises mono-, di- and tri- ester components, it is preferred that the weight ratio of the mono-ester component of the quaternary ammonium fabric softening material to the fatty complexing agent is preferably from 5:1 to 1:5, more preferably 4:1 to 1:4, most  
15 preferably 3:1 to 1:3, e.g. 2:1 to 1:2.

The method for calculating the mono-ester linked component of the quaternary ammonium material is as described in WO-A1-03/022970.

20

If the fatty complexing agent is a fatty alcohol it may also act as a co-active softener.

### Perfume

25

The compositions of the invention preferably comprise one or more perfumes.

30

It is well known that perfume is provided as a mixture of various components.

It is preferred that at least a quarter (by weight) or more, preferably a half or more of the perfume components have a

ClogP of 2.0 or more, more preferably 3.0 or more, most preferably 4.5 or more, e.g. 10 or more.

Suitable perfumes having a ClogP of 3 or more are disclosed  
5 in US 5500137.

ClogP is calculated using the "ClogP" program (calculation of hydrophobicities as logP (oil/water)) version 4.01, available from Daylight Chemical Information Systems Inc of  
10 Irvine California, USA.

The perfume is preferably present in an amount from 0.01 to 10% by weight, more preferably 0.05 to 5% by weight, most preferably 0.1 to 4.0% by weight, e.g. 0.2 to 0.6% by weight  
15 based on the total weight of the composition.

#### Liquid Carrier

The liquid carrier employed in the instant compositions is  
20 preferably water due to its low cost relative availability, safety, and environmental compatibility. The level of water in the liquid carrier is preferably more than about 50%, more preferably more than about 80%, most preferably more than about 85%, by weight of the carrier. The level of  
25 liquid carrier is preferably greater than about 50%, more preferably greater than about 65%, most preferably greater than about 70% by weight, based on the total weight of the composition. Mixtures of water and a low molecular weight, e.g. <100, organic solvent, e.g. a lower alcohol such as  
30 ethanol, propanol, isopropanol or butanol are useful as the carrier liquid. Low molecular weight alcohols including monohydric, dihydric (glycol, etc.) trihydric (glycerol, etc.), and polyhydric (polyols) alcohols are also suitable

carriers for use in the compositions of the present invention.

#### Other co-active softeners

5

Co-active softeners for the cationic surfactant may also be incorporated in an amount from 0.01 to 20% by weight, more preferably 0.05 to 10%, based on the total weight of the composition. Preferred co-active softeners include fatty esters, and fatty N-oxides.

10

Preferred fatty esters include fatty monoesters, such as glycerol monostearate. If GMS is present, then it is preferred that the level of GMS in the composition, is from 0.01 to 10 wt%, based on the total weight of the composition.

15

The co-active softener may also comprise an oily sugar derivative. Suitable oily sugar derivatives, their methods of manufacture and their preferred amounts are described in WO-A1-01/46361 on page 5 line 16 to page 11 line 20, incorporated herein.

20

#### Polymeric viscosity control agents

25

It is useful, though not essential, if the compositions comprise one or more polymeric viscosity control agents. Suitable polymeric polymeric viscosity control agents include nonionic and cationic polymers, such as hydrophobically modified cellulose ethers (e.g. Natrosol Plus, ex Hercules), cationically modified starches (e.g. Softgel BDA and Softgel BD, both ex Avebe). A particularly preferred viscosity control agent is a copolymer of

30

methacrylate and cationic acrylamide available under the tradename Flosoft 200 (ex SNF Floerger).

5 Nonionic and/or cationic polymers are preferably present in an amount of 0.005 to 5wt%, more preferably 0.01 to 4wt%, most preferably 0.015 to 2wt%, e.g. 0.02 to 0.08wt%, based on the total weight of the composition.

### Electrolytes

10

An electrolyte may be present in the composition.

15 Preferred electrolyte include salts of multi-valent anions such as sulphate is particularly preferred. Preferred counter ions for this anion included alkaline earth metals, ammonium or alkalimetals.

20 Particularly preferred are alkalimetal cations or ammonium. Typically preferred are sodium, potassium or ammonium salts. Sodium sulphate is particularly preferred.

25 It is preferred that the salt of the multivalent anion is substantially water soluble. Preferably, the salt of the multivalent anion has a solubility in excess of 1 gram per litre, preferably in excess of 25 grams per litre.

The electrolyte may comprise a salt of a univalent anion. It is preferred that the salt of the univalent anion comprises an alkali metal or alkaline earth metal salt. It is particularly preferred that the cation is sodium, potassium or ammonium. The univalent anion may be any suitable univalent anion. It is preferably an inorganic anion, and is preferably a halide, most preferably chloride.

There may be more than one salt of a univalent anion present. Particularly preferred are calcium chloride, sodium chloride, ammonium halide, rare earth halides, such as lanthanum chloride and alkali metal salts of organic acids such as sodium acetate and sodium benzoate.

Preferably, the total weight of electrolyte present is from 0.5-3.0%, more preferably 1.0-2.0%, most preferably 1.0-1.5% by weight, based on the total weight of the composition.

The salt of the univalent anion is preferably substantially water soluble. Preferably, it has a solubility in excess of 1 gram per litre, more preferably in excess of 20 grams per litre.

#### Further Optional Ingredients

Other optional nonionic softeners, bactericides, soil-releases agents may also be incorporated in the compositions of the invention.

The compositions may also contain one or more optional ingredients conventionally included in fabric conditioning compositions such as pH buffering agents, perfume carriers, fluorescers, colourants, hydrotropes, antifoaming agents, antiredeposition agents, polyelectrolytes, enzymes, optical brightening agents, anti-shrinking agents, anti-wrinkle agents, anti-spotting agents, antioxidants, sunscreens, anti-corrosion agents, drape imparting agents, anti-static agents, anti-mould agents, ironing aids and dyes.

**Product Form**

At ambient temperature, the product comprises a liquid, more preferably an aqueous liquid, most preferably an aqueous dispersion of the quaternary ammonium softening material.

**Product Use**

10 The composition is preferably used in the rinse cycle of a home textile laundering operation, where, it may be added directly in an undiluted state to a washing machine, e.g. through a dispenser drawer or, for a top-loading washing machine, directly into the drum. Alternatively, it can be  
15 diluted prior to use. The compositions may also be used in a domestic hand-washing laundry operation.

It is also possible, though less desirable, for the compositions of the present invention to be used in  
20 industrial laundry operations, e.g. as a finishing agent for softening new clothes prior to sale to consumers.

**Preparation**

25 The compositions of the invention may be prepared according to any suitable method.

In a first preferred method, the quaternary ammonium material, nonionic material and perfume are heated together  
30 until a co-melt is formed. Water is then heated and the co-melt is added to water with stirring. The mixture is then allowed to cool. In an alternative method, the perfume can

be added to the mixture after the co-melt is formed, e.g. at any time during the cooling stage.

### Examples

5

The invention will now be illustrated by the following non-limiting examples. Further modifications will be apparent to the person skilled in the art.

10 All values are % by weight of the active ingredient unless stated otherwise.

Samples A to J were prepared in a standard 3l rig with a Janke Kunkel mill using the following process:

15

The DEQA, fatty alcohol and nonionic material (if present) were co-melted and then added to water at 65 °C over 2 minutes with agitation (200 rpm). Mixing was continued for a further 10 minutes and then preservative and dye added.

20

The resulting mixture was removed from heat and perfume added with mixing and over 5 minutes during cooling. The polymer was then added.

Table 1

25

	A	B	C	D	E	F
DEQA (1)	4.98	4.98	4.98	4.98	4.98	4.98
Fatty alcohol (2)	0.42	0.42	0.42	0.42	0.42	0.42
Perfume	0.34	0.34	0.34	0.34	0.34	0.34
Dye	0.001	0.001	0.001	0.001	0.001	0.001
Polymer (3)	0.03	0.03	0.03	0.03	0.03	0.03
Nonionic (4)	-	2.0	-	-	-	-
Nonionic (5)	-	-	2.0	-	-	-
Nonionic (6)	-	-	-	2.0	-	-

Nonionic (7)	-	-	-	-	2.0	-
Nonionic (8)	-	-	-	-	-	2.0
Preservative	0.08	0.08	0.08	0.08	0.08	0.08
Water	To 100	To 100	To 100	To 100	To 100	To 100

(1) di(acyloxyethyl) (2-hydroxyethyl) methyl ammonium methyl sulphate where the acyl group is derived from fully hydrogenated tallow.

- 5 (2) Stenol 1618L, ex Cognis  
 (3) Natrasol 331, ex Hercules  
 (4) Tergitol 15-S-3, ex Union Carbide  
 (5) Tergitol 15-S-5, ex Union Carbide  
 (6) Tergitol 15-S-7, ex Union Carbide  
 10 (7) Lutensol TO3, ex BASF  
 (8) Coco 5 EO (available as Genapol C050, ex Clariant)

Table 2

	G	H	I	J	K
DEQA (1)	4.98	4.98	4.98	4.98	4.98
Fatty alcohol (2)	0.42	0.42	0.42	0.42	0.42
Perfume	0.34	0.34	0.34	0.34	0.34
Dye	0.001	0.001	0.001	0.001	0.001
Polymer (3)	0.03	0.03	0.03	0.03	0.03
Nonionic(9)	2.0	-	-	-	-
Nonionic (4)	-	0.5	1.0	-	-
Nonionic (7)	-	-	-	0.5	1.0
Preservative	0.08	0.08	0.08	0.08	0.08
Water	To 100	To 100	To 100	To 100	To 100

- 15 (1) as above  
 (2) as above  
 (3) as above  
 (4) as above  
 (7) as above  
 20 (9) Coco 20EO (Genapol C-200, ex Clariant)

Table 3

	L	M
DEQA (1)	4.98	4.98
Fatty alcohol (2)	0.42	0.42
Perfume	0.34	0.34
Dye	0.002	0.002
Polymer (3)	0.03	0.03
Nonionic(10)	2.0	-
Nonionic (11)	-	2.0
Water	To 100	To 100

- 5 (1) as above  
(2) as above  
(3) as above  
(10) polyethylene glycol monodecyl ether (KX-NS12030, ex Nippon Shokubai)
- 10 (11) polyethylene glycol tetradodecyl ether (KX-NS14030, ex Nippon Shokubai)

Example 1; viscosity evaluation

- 15 Viscosity was measured upon storage at various temperatures. Measurements were made at  $106s^{-1}$  at ambient temperature using a Haake Rotoviscometer RV20 NV Bob and Cup.

Sample A was stored at 37°C, 41°C, 45°C and 50°C. Viscosity  
20 data is given in the following table:

Table 4

Temp (°C)	Time (weeks)					
	0	4	6	8	10	12
37	117.7	133.8	110	92	94	82
41	117.7	124.8	123	78	79	72
45	117.7	130.7	78	87	Gelled	-
50	117.7	95.7	88	127	Gelled	-

- 5 The results demonstrate that storage stability was particularly problematic at very high temperatures.

10 Samples B to M were stored at 45°C and 50°C. The viscosity results are given in the following table. In the following tables, "G" denotes gelled, "P" denotes pearlesced, "PS" denotes phase separation, "F" denotes flocculated, and "S" denotes solid.

15 Table 5; storage at 45°C

Sample	Time (weeks)									
	0	2	4	6	7	8	9	10	11	12
B	111	-	123	57	-	58	-	61	-	79
C	60	13	8	P	-	-	-	-	-	-
D	6	-	15	16	-	F	-	-	-	-
E	150	-	156	193	-	109	-	92	-	122
F	10	-	7	6	-	16	-	P	-	-
G	10	-	7	5	-	16	-	P	-	-
H	102	118	95	89	-	78	-	-	S	-
I	100	114	87	67	-	78	-	-	123	-
J	101	83	98	-	99	-	135	-	-	-
K	124	107	99	-	93	-	124	-	-	-
L	109	-	97	89	-	72	-	-	-	124
M	156	-	132	144	-	171	-	-	-	202

Table 6; storage at 50°C

Sample	Time (weeks)									
	0	2	4	6	7	8	9	10	11	12
B	111	-	83	64	-	47	-	71	Gel	-
C	60	9	PS	-	-	-	-	-	-	-
D	6	-	15	F	S	-	-	-	-	-
E	150	-	111	97	-	62	-	83	-	G
F	10	-	6	5	-	PS				
G	10	-	6	5	-	PS	-	-	-	-
H	102	72	43	46	-	88	-	-	S	-
I	100	47	41	-	-	63	-	-	S	-
J	101	82	82	-	124	-	S	-	-	-
K	124	80	102	-	103	-	124	-	-	-
L	109	-	82	59	-	48	-	-	-	PS
M	156	-	117	135	-	198	-	-	-	PS


CLAIMS

1. A fabric conditioning composition comprising:

5 (a) an ester-linked quaternary ammonium fabric softening material; and

(b) a nonionic material represented by formula (I):-

10



(I)

15

wherein R and R' are independently selected from C<sub>1</sub> to C<sub>15</sub> optionally substituted alkyl, alkenyl, hydroxyalkyl and benzyl groups and the combined number of carbons in R and R' is from 7 to 16, n is from 1 to 9 and a is 2 or 3.

20

2. A composition as claimed in claim 1 wherein, in the nonionic material, n is from 2 to 8.

25 3. A composition as claimed in claim 1 or claim 2 wherein, in the nonionic material, n is from 2 to 6.

4. A composition as claimed in any one of the preceding claims wherein, in the nonionic material, n is from 2 to

30

5.

- 25 -


5. A composition as claimed in any one of the preceding claims wherein, in the nonionic material, n is from 2 to 4.

5 6. A composition as claimed in any one of the preceding claims wherein, in the nonionic material, the total number of carbons, R + R', is from 8 to 15.

10 7. A composition as claimed in any one of the preceding claims wherein, in the nonionic material, the total number of carbons, R + R', is from 10 to 15.


15 8. A composition as claimed in any one of the preceding claims wherein, in the nonionic material, the total number of carbons, R + R', is from 11 to 15.

20 9. A composition as claimed in any one of the preceding claims wherein the quaternary ammonium cationic softening material is represented by formula (I):




25 wherein each R is independently selected from a C<sub>5-35</sub> alkyl or alkenyl group, R<sup>1</sup> represents a C<sub>1-4</sub> alkyl or hydroxyalkyl group or a C<sub>2-4</sub> alkenyl group,

30



n is 0 or an integer selected from 1 to 4, m is 1, 2 or 3 and denotes the number of moieties to which it refers that pend directly from the N atom, and  $\text{X}^-$  is an anionic group, such as halides or alkyl sulphates, e.g. chloride, methyl sulphate or ethyl sulphate.

10. The use of a nonionic material of formula:-




wherein R and R' are independently selected from  $\text{C}_1$  to  $\text{C}_{15}$  optionally substituted alkyl, alkenyl, hydroxyalkyl and benzyl groups and the combined number of carbons in R and R' is from 7 to 16, n is from 1 to 9 and a is 2 or 3

in a fabric conditioning composition to improve the elevated temperature storage stability of the fabric conditioning composition.

Abstract

A fabric conditioning composition comprises (a) an ester linked quaternary ammonium fabric softening material; and  
5 (b) a nonionic material represented by formula (I):-



wherein R and R' are independently selected from C<sub>1</sub> to C<sub>15</sub> optionally substituted alkyl, alkenyl, hydroxyalkyl and  
15 benzyl groups and the combined number of carbons in R and R' is from 7 to 16, n is from 1 to 9 and a is 2 or 3. The nonionic material is used to improve high temperature storage stability of the composition.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINE(S) OR MARK(S) ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**